



## Technical Specifications



### ACDC R32



Items	Unit	9000BTU	12000BTU	18000BTU	24000BTU
Mode		DWGA21-ACDCBLW-09KR2(EU)	DGWA21-ACDCBLW-12KR2(EU)	DGWA5-ACDCBLW-18KR2(EU)	DGWA6-ACDCBLW-24KR2(EU)
Solar Power Voltage	V	80~380	80~380	80~380	80~380
Grid Power Voltage	V/Hz	208V~240V/50~60Hz	208V~240V/50~60Hz	208V~240V/50~60Hz	208V~240V/50~60Hz
Cooling Capacity	W	2700(800-3500)	3500(800~3900)	5010(1300~5850)	6400(1800~7800)
Cooling power input	W	620(150-1000)	860(150~1100)	1250(220~1670)	1690(340~2550)
Heating Capacity	W	3100(900-4000)	3500(900~4200)	5010(1300~5200)	7030(1800~7800)
Heating power input	W	680(150-1150)	870(150~1200)	1200(220~1420)	1780(320~2190)
EER	W/W	4.35/14.50	3.70/12.50	3.60/12.25	3.60/12.25
Indoor unit Dimension (WxHxD) mm		840x205x295	840x205x295	1080x330x237	1080x330x237
Indoor unit Packing (WxHxD) mm		920x290x360	920x290x360	1140x300x382	1140x362x300
Outdoor unit Dimension (WxHxD) mm		802x564x323	802x564x323	802x564x323	900x700x337
Outdoor unit Packing (WxHxD) mm		910x622x405	910x622x405	910x622x405	1006x755x418

