

80W Foldable Solar Charger

Max. Power: (Pmx)	80W
Voltage at Pmax: (Vmp)	17.3V
Current at Pmax: (Imp)	4.62A
Open Circuit Voltage: (Voc)	20.07V
Short Circuit Current: (Isc)	4.89A
Output Connector	DC5521
Standard Test Condition: AM1.5, 1KW/m2, 25°C	

Safety Tips

- * Do not drop or bend the solar panel (the angle is more than 30°) or the panel will be broken.
- * Do not immerse the solar panel in water.
- * Do not clean the solar panel with water, with the wet cloth gently scrub it.
- * Do not user or store the solar panel near sources of heat such as a fire or heater.
- * Do not put the solar panel into a fire or apply direct heart to it.
- * Do not pierce the solar panel casing with a nail or other sharp object, break it open with a hammer,or step on it.
- * Do not attempt to disassemble the solar panel in any way.
- * This product cannot contact with strong corrosive objects.
- * Do not charge automotive battery directly.

80W Foldable Solar Charger

Max. Power: (Pmx)	80W
Voltage at Pmax: (Vmp)	17.3V
Current at Pmax: (Imp)	4.62A
Open Circuit Voltage: (Voc)	20.07V
Short Circuit Current: (Isc)	4.89A
Output Connector	DC5521
Standard Test Condition: AM1.5, 1KW/m2, 25°C	

Safety Tips

- * Do not drop or bend the solar panel (the angle is more than 30°) or the panel will be broken.
- * Do not immerse the solar panel in water.
- * Do not clean the solar panel with water, with the wet cloth gently scrub it.
- * Do not user or store the solar panel near sources of heat such as a fire or heater.
- * Do not put the solar panel into a fire or apply direct heart to it.
- * Do not pierce the solar panel casing with a nail or other sharp object, break it open with a hammer,or step on it.
- * Do not attempt to disassemble the solar panel in any way.
- * This product cannot contact with strong corrosive objects.
- * Do not charge automotive battery directly.